

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 034 752 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

13.09.2000 Bulletin 2000/37

(51) Int. Cl.⁷: A61F 2/06

(21) Application number: 00104536.8

(22) Date of filing: 13.03.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 11.03.1999 US 266113

(71) Applicant: MEDTRONIC, INC.

Minneapolis, Minnesota 55432-3576 (US)

(72) Inventors:

• Mohn, Jr, Michael A.
San Diego, California 99129 (US)

• Stiger, Mark L.

El Cajon, California 92019 (US)

• Lentz, David J.

La Jolla, California 92037 (US)

• Cruz, Rey O.

National City, California 91950 (US)

(74) Representative:

Hughes, Andrea Michelle

Frank B. Dehn & Co.,

European Patent Attorneys,

179 Queen Victoria Street

London EC4V 4EL (GB)

(54) Method of stent retention to a delivery catheter balloon - braided retainers

(57) A stent delivery balloon catheter system includes a pair of retainers which are anchored to the catheter to hold the stent against the balloon until the stent is to be deployed. Each retainer is made of filaments which are woven together to form a braided tube shaped structure. Further, each retainer has one end which is anchored to the catheter while the free end of the retainer overlaps a respective end of the stent. Upon

inflation of the balloon for deployment of the stent, the balloon also urges against each retainer. This causes the woven tube structure of the retainer to expand, and thereby shorten. As the retainers shorten, they also withdraw from the stent, and thereby release the stent for deployment.




Figure 1

BEST AVAILABLE COPY

EP 1 034 752 A1

Description

[0001] The present invention pertains generally to stent delivery catheters. More particularly, the present invention pertains to stent retainers which are incorporated into a stent delivery system for the purpose of holding a stent against the balloon of a balloon catheter during its advancement into the vasculature of a patient. The present invention is particularly, but not exclusively, useful as a stent retainer which relies on a mechanical reconfiguration of the retainer to separate the retainer from the stent during its deployment.

[0002] The introduction of a foreign object into the vasculature of a patient presents obviously complex problems. Specifically, both the object and its delivery system must be capable of being advanced into the vasculature for its intended purpose, without unduly traumatizing the patient. Further, this advancement must be accomplished accurately and with great precision. To this end, interventional systems are typically designed to be as smooth as possible, to have as small a profile as possible, and to be as easily controlled as possible. These design characteristics, however, do not directly address the different set of problems which are confronted when, after being advanced into the vasculature by a delivery system, an object is thereafter deployed or disengaged from the delivery system to remain in situ.

[0003] In order to deploy or disengage an object from a delivery system in the vasculature of a patient, it is necessary to somehow reconfigure the object and the delivery system for this purpose. The structures used for these functions, however must not be allowed to interfere with the aforementioned task of advancing the object into the vasculature. Furthermore, the structure used to deploy or disengage an object from its delivery system must not itself create problems which would traumatize the patient while the system is in the vasculature. In sum, it is important for a delivery system to function reliably and safely. It happens that several devices have been disclosed which are directed toward this result.

[0004] U.S. Patent No.3,902,501 which issued to Citron et al. for an invention entitled "Endocardial Electrode," and which is assigned to the same assignee as the present invention, discloses an interventional device for the deployment of a medical electrode. Specifically, the invention disclosed by Citron et al. incorporates a shroud which is axially fixed in its position on the device. As so positioned, the shroud overlaps and holds the exposed ends of the electrode's tines against the electrode body until the tines are to be deployed. To deploy the tines, a balloon on the electrode body is inflated to withdraw the tines from the shroud. Another example of this same basic deployment scheme, but for a slightly different application, is provided by U.S. Patent No. 4,950,227 which issued to Savin et al. for an invention entitled "Stent Delivery System." According to the invention of Savin et al., a stent is positioned over the balloon

of a balloon catheter. A pair of sleeves are axially fixed on the device with one end of each sleeve anchored to the catheter while the other end overlaps a respective end of the stent to hold the stent on the balloon. The result is that the sleeve is fixed at an axial location on the catheter. In an action similar to that disclosed for the device of Citron et al., when the balloon is inflated, the ends of the stent are withdrawn from their respective sleeve and the stent is thus deployed.

[0005] A difficulty not resolved by either the Citron et al. device or the Savin et al. device is the fact that the sleeves of Savin et al., like the shroud of Citron et al., are axially fixed and therefore substantially immobile. Stated differently, both of these devices rely solely on a change in the configuration of the object being deployed to disengage the object from the shroud or sleeves which hold the object against the balloon. Neither of these devices relies on a mechanical change in either the shroud or the stent for this disengagement. Thus, because the shroud (Citron et al.) or the sleeves (Savin et al.) do not mechanically withdraw axially from the tines or stent during deployment less of the tines or stent can be covered by the respective shroud or sleeves than would otherwise be possible prior to deployment. Consequently, with less overlapping coverage, there is an increased risk of premature dislodgment of the object being deployed, and an increased risk of a system malfunction during deployment.

[0006] In light of the above it is an object of the present invention to provide a system for selectively holding a stent on a balloon delivery catheter which incorporates retainers that will mechanically shorten with an inflation of the balloon to facilitate disengagement of the stent from the system. Still another object of the present invention, is to provide a system for selectively holding a stent on a balloon delivery catheter which effectively covers the projecting ends of a stent to protect the patient from snags, hang-ups or entanglements that might otherwise occur during advancement of the system into the vasculature of the patient. Yet another object of the present invention is to provide a system for selectively holding a stent on a balloon delivery catheter which includes stent retainers that revert to a low profile after stent deployment to facilitate withdrawal of the system from the vasculature of the patient. Another object of the present invention is to provide a system for selectively holding a stent on a delivery catheter which is relatively easy to manufacture, simple to use and comparatively cost effective.

[0007] In accordance with one aspect of the present invention, there is provided a system for selectively holding a stent (on a delivery catheter which comprises:

an inflatable balloon defining a longitudinal axis;
a first plurality of mutually juxtaposed filaments;
a second plurality of mutually juxtaposed filaments woven with said first plurality of filaments to create a braided tube having a proximal end and a distal

end with a length therebetween;

means for anchoring said proximal end of said braided tube to said balloon to position said distal end of said tube over a proximal portion of said stent when said stent is mounted on said balloon to hold said stent against said balloon, said tube being positioned with said filaments of said first plurality helically disposed with a positive pitch relative to said axis and said filaments of said first plurality helically disposed with a positive pitch relative to said axis and said filaments of said second plurality helically disposed with a negative pitch relative to said axis; and

means for inflating said balloon to urge said balloon against said tube to increase said positive pitch and increase said negative pitch of respective said filaments to shorten said length of said tube to withdraw said tube from said stent to release said stent from said balloon.

[0008] In accordance with another aspect, there is provided a stent delivery balloon catheter system which comprises:

a catheter,

an inflatable balloon having a first and a second end with a working section therebetween, said balloon defining a longitudinal axis;

a stent having a first end and a second end, said stent being positioned on said balloon over said working section; and

a tubular shaped retainer having a first end and a second end and being moveable between a first configuration wherein said retainer has a first length and a second configuration wherein said retainer has a second length, said first length being greater than said second length, and further wherein said retainer has said first end thereof anchored to said catheter and said second end thereof overlaps a portion of said stent to hold said stent on said balloon while said balloon is deflated and said retainer is in said first configuration, said second end of said retainer withdrawing from said stent to release said stent from said catheter when said balloon is inflated to move said retainer into said second configuration.

[0009] In accordance with another aspect, there is provided a stent delivery balloon catheter system which comprises:

an inflatable balloon having a proximal cone and a distal cone with a working section therebetween;

a stent having a proximal end and a distal end, said stent being positioned on said balloon over said working section;

a proximal retainer having a proximal end and a distal end with said proximal end thereof anchored to

said balloon to position said proximal retainer over said proximal cone of said balloon and position said distal end thereto in an overlapping relationship with said proximal end of said stent, said proximal retainer having a length;

a distal retainer having a proximal end and a distal end with said distal end thereof anchored to said balloon to position said distal retainer over said distal cone of said balloon to position said distal retainer over said distal cone of said balloon and position said proximal end thereof in an overlapping relationship with said distal end of said stent, said distal retainer having a length; and

means for inflating said balloon to shorten said respective lengths of said proximal retainer and said distal retainer to release said stent from said system as said stent is deployed by inflation of said balloon.

[0010] During advancement of the system into the vasculature of a patient, and prior to deployment of the stent, the retainers are used to hold the stent on the catheter. During actual deployment of the stent, however, as the balloon is being inflated the retainers are designed to mechanically withdraw from the stent and thereby facilitate disengagement of the stent from the system. Finally, after deployment of the stent, the retainers collapse with the deflated balloon to provide a low profile for the system during its withdrawal from the patient's vasculature.

[0011] In use, a device in accordance with the present invention a stent is initially positioned over the central, or working, portion of an elongated inflatable balloon. Each of the retainers is then positioned over a respective cone at the ends of the balloon and each retainer has one end which is anchored to the catheter, the other, unanchored end is then positioned to overlap an end of the stent. For example, the proximal end of the proximal retainer is anchored, or bonded, to the catheter, while the distal end of the proximal retainer overlaps the proximal end of the stent. Similarly, the distal end of the distal retainer is anchored to the catheter while the proximal end of the distal retainer overlaps the distal end of the stent.

[0012] The structure of both the proximal retainer and the distal retainer are essentially the same. Specifically, each retainer includes a first plurality of filaments which are woven together with a second plurality of filaments to create a braided tube. With this structure, when the retainer is mounted on the catheter, the first plurality of filaments are helically disposed with a positive pitch angle relative to the longitudinal axis of the catheter, and the second plurality of filaments are likewise helically disposed, but with a negative pitch angle. The overall result is that the retainer is axially movable whenever the retainer expands in response to an inflation of the balloon. More specifically, this movement is between a first configuration wherein the retainer has a

first length, and a second configuration wherein the retainer has a shorter second length. During a transition from the first to the second configuration, both the positive and negative helical pitches are increased. Importantly, as indicated, the first length is longer than the second length.

[0013] In the operation of the system of the present invention, the stent with overlapping retainers is advanced into the vasculature of a patient. Once the stent is properly positioned for deployment in the vasculature, the balloon is inflated. Due to the inflation of the balloon, the stent is expanded by the working section of the balloon. At the same time, the retainers are expanded by the cones of the balloon. With this expansion, the helical pitch of filaments in both of the retainers is increased and the retainer is actually shortened in an axial direction. The combined effect of the expanding stent and the shortened retainers causes the retainers to withdraw from the stent and thereby disengage the stent from the system. Subsequently, upon deflation of the balloon, the retainers collapse with the balloon to facilitate withdrawal of the system from the vasculature, and thus leave the stent implanted at the desired positions.

[0014] The novel features of this invention, as well as the invention itself, both as to its structure and its operation, will be best understood from the accompanying description, given by way of example only, taken in conjunction with the accompanying drawings, in which similar reference characters refer to similar parts, and in which:

Figure 1 is a side elevational view of the major components at the distal end of a stent delivery system according to the present invention with the components separated from each other for clarity;

Figure 2 is a comparison view of the braid component of a stent retainer according to the present invention with the retainer shown in an elongated configuration and in a compressed configuration;

Figure 3A is a view of the stent delivery system of the present invention inserted into a vessel within a stenosis in the vasculature of a patient prior to inflation of the balloon for deployment of the stent;

Figure 3B is a cross-sectional view of the stent delivery system in the configuration shown in Fig. 3A;

Figure 4A is a view of the stent delivery system shown in Figure 3A with the balloon inflated to deploy the stent;

Figure 4B is a cross-sectional view of the stent delivery system in the configuration shown in Fig. 4A;

Figure 5 is a view of the stent delivery system shown in Figures 3A and 4A after the stent has been deployed and the balloon deflated for withdrawal from the vasculature, the stent is shown in cross-section for clarity;

Figure 6 is a perspective view of a stent retainer according to the present invention;

Figures 7A-H are each a cross sectional view of various embodiments for the stent retainer of the present invention as seen along the line 7-7 in Figure 6; and

Figure 8 is a perspective view of a stent delivery system of the present invention employing an alternative embodiment for the retainers.

[0015] Referring initially to Figure 1, a stent delivery balloon catheter system in accordance with the present invention is shown and generally designated 10. As shown in Figure 1 the system 10 includes an elongate inflatable balloon 12 of a type well known in the pertinent art, a stent 14, a proximal retainer 16 and a distal retainer 18. More specifically, the balloon 12 is an integral part of a catheter 20 which is formed with an inflation lumen. The system 10 also includes a fluid pump (not shown) which is in fluid communication with the balloon 12 via the inflation lumen. Thus, as intended for the present invention, the fluid pump can be activated to either inflate or deflate the balloon 12.

[0016] As indicated in Figure 1, the balloon 12 has a working section 22 which is intermediate a proximal cone 24 and a distal cone 26. Although the balloon 12 is shown in an inflated configuration in Figure 1, it is to be appreciated that the overall configuration of the balloon 12, and specifically the configurations of working section 22 and cones 24, 26, will be changed when the balloon 12 is deflated. As clearly set forth below, this change in configuration of the balloon 12 between an inflated and a deflated configuration is important to the operation of the system 10.

[0017] During the assembly of the system 10, the stent 14 is positioned over the working section 22 and located to surround the balloon 12. Additionally, the proximal retainer 16 is positioned over the proximal cone 24 to surround the balloon 12, and the distal retainer 18 is similarly positioned over the distal cone 26 of the balloon 12. More specifically, in the initial assembly of the system 10 the balloon 12 is deflated. With the balloon 12 deflated, the stent 14 is positioned over the working section 22 and held against the balloon 12 in a manner well known in the pertinent art, such as by crimping. Once the stent 14 is in place on the balloon 12, the retainers 16, 18 are properly attached to the system 10. To do this, the proximal end 28 of proximal retainer 16 is anchored to the catheter 20 in a manner well known in the pertinent art, such as by heat bonding to the balloon 12. Likewise, the distal end 30 of distal retainer 18 is anchored to the catheter 20. It can be noted that the balloon 12 of the system 10 is, in all important respects, a conventional angioplasty balloon. No specific materials are required, and no specific dimension or configuration for the working section 22 or the cones 24, 26 are required.

[0018] Figure 1 also shows that, due to their relative

lengths and the selected anchor points where the retainers 16, 18, are attached to the catheter 20, when the stent 14 and the two retainers 16, 18 have been positioned on the balloon 12 there will be some overlap between these components of the system 10. Specifically, the distal end 32 of proximal retainer 16 will overlap the proximal end 34 of stent 14 by a distance 36. Similarly, the proximal end 38 of distal retainer 18 will overlap the distal end 40 of stent 14 by a distance 42. The exact magnitude of the distances 36, 42 are a matter of design choice, but they should be selected with the capabilities of the respective retainers 16 and 18 in mind. An appreciation of these capabilities will, perhaps, be best obtained by reference to Figure 2.

[0019] In Figure 2, the proximal retainer 16 is used as an example and is shown in two configurations. The configuration for retainer 16 shown in the upper part of the drawing corresponds to the condition wherein balloon 12 is deflated. On the other hand, the configuration for retainer 16' which is shown in the lower part of the drawing corresponds to the condition wherein balloon 12 is inflated. The capability for retainer 16 to move between these two configurations is, in large part, due to the structure of the retainer 16. As shown, the retainer 16 includes a first plurality of juxtaposed filaments 44. Also shown is a second plurality of juxtaposed filaments 46 which are interwoven with the filaments 44 to create a braided tube-like structure. It is to be appreciated that in this braided condition, the filaments 44 and the filaments 46 each assume a generally helical configuration which can be characterized by a pitch angle. For this purpose, consider the filament 44a as an example of the first plurality of filaments 44, and the filament 46a as an example of the second plurality of filaments 46. When the balloon 12 is deflated, it will be seen that the filaments 44 establish a positive pitch angle $+\alpha$ relative to an axis 48 and the filaments 46 establish a negative pitch angle $-\alpha$ relative to the axis 48. For purposes of the present invention, the axis 48 is taken to be the longitudinal axis defined by the retainer 16, 18. Incidentally, when the retainers 16, 18 are mounted on the catheter 20, axis 48 will also be the longitudinal axis of the catheter 20.

[0020] When the balloon 12 is inflated, the filaments 44, 46 will move, the pitch angle of the filaments will change, and the retainer 16 will assume the general configuration shown in Figure 2 for retainer 16'. For the retainer 16' shown in Figure 2, it is to be appreciated that, when the balloon 12 is inflated the filament 44a will establish a positive pitch angle $+\beta$ and that the filament 46a will establish a negative pitch angle $-\beta$. Importantly, the pitch angles $\pm\alpha$ are smaller than the pitch angles $\pm\beta$. As a consequence of this change in configuration, the length 50 of the proximal retainer 16 (with balloon 12 deflated) is longer than the length 52 of the proximal retainer 16' (with balloon 12 inflated). For the present invention, the filaments 44, 46 can be made of filaments, or groups of filaments (yarn), and be of any

metallic or plastic material in either a monofilament or multi-filament configuration, or in general, any material deemed suitable for the application thus described herein, such as nylon monofilament, stainless steel wire, glass fibers or an elastomer impregnated with a material such as graphite for enhanced lubricity. A suitable elastomer for this purpose is a PolyEther Block Amide (PEBA) available under the name PEBAX® obtainable from the Elf ATOChem Corporation, Philadelphia, PA (e.g. PEBAX 5533). In any case, the significance of the interactions between filaments 44, 46 during the shortening of the retainer 16, 18 may be best appreciated by considering the operation of the system 10.

[0021] In the operation of the system 10 of the present invention, the catheter 20 is advanced over a guidewire 54 into a vessel 56 of a patient's vasculature. Specifically, the catheter 20 is advanced into the vasculature until the stent 14 is positioned across the stenosis 58, or some type of obstruction or lesion in the vessel 56, where it is to be deployed (see Figure 3A). Prior to deployment of the stent 14, the dimensional relationships between the stent 14, the proximal retainer 16 and the distal retainer 18 are, perhaps, best seen in Fig. 3B.

[0022] Once the stent 14 is properly positioned, the balloon 12 is inflated to expand the stent 14' to a configuration, as shown in Figure 4A. As is well known, this allows the stent 14' to act as a support structure for maintaining a patency in the vessel 56. For the present invention, and still referring to Figure 4A, it should also be noted that the retainers 16', 18' have withdrawn from the stent 14'. Specifically, as previously disclosed with reference to Figure 2, upon inflation of the balloon 12, the retainers 16, 18 are mechanically shortened by more than the respective overlap distances 36, 42. Thus, the retainers 16', 18' withdraw from the stent 14'. This separates the retainers 16', 18' from the stent 14' so that they no longer act to hold the stent 14' on the balloon 12. With deployment of the stent 14, the now-changed dimensional relationships between the stent 14', the proximal retainer 16' and the distal retainer 18' are best seen in Fig. 4B. After deployment of the stent 14', the balloon 12 is deflated.

[0023] Upon deflation of the balloon (see Figure 5) the expanded stent 14' will retain its expanded configuration and will be separated from the system 10. Thus, the expanded stent 14' remains in situ. The retainers 16', 18', however, no longer cooperate with the stent 14 and they therefore collapse with the balloon 12 as it returns to its deflated configuration. They do not reengage with the stent 14' and, accordingly, the retainers 16, 18 release the expanded stent 14' from the system 10. As can then be appreciated with reference to Figure 5, after balloon 12 has been deflated, the balloon 12 and the retainers 16, 18 are withdrawn from vessel 56 of the patient's vasculature. As will be appreciated by the skilled artisan, the collapse of the retainers 16, 18 can be caused by biasing the retainers 16, 18 toward their

collapsed configuration. This can be accomplished in several ways, such as by specifically weaving the filaments 44, 46 in a manner to generate the bias, or by use of a biasing sleeve 60 which can be incorporated into the retainer 16, 18.

[0024] In Figure 6, an exemplary retainer 16 is shown for purposes of disclosing possible embodiments for the retainer 16 which incorporate a biasing sleeve 60. As shown in Figure 6, the retainer 16 is generally tubular shaped. With this shape the retainer 16 will have both an outer surface 62 and an inner surface 64. As will be appreciated by the skilled artisan, either or both surfaces 62, 64 can be entirely or partially covered by a biasing sleeve. Further, it will be appreciated that the retainer 16 can be divided into longitudinal segments which may, or may not, include braided filaments 44, 46. Several possibilities are shown in Figures 7A-H.

[0025] Figure 7A illustrates an embodiment for the retainer 16 wherein there is only the filaments 44, 46 and no additional structure. For this embodiment, the collapsing bias of the retainer 16 must be provided by the filaments 44, 46 themselves. For the embodiment of retainer 16 shown in Figure 7B, however, a biasing sleeve 60 is shown which covers the entire outer surface 62. For this embodiment as with all other embodiments which incorporate biasing sleeves, it is to be appreciated that the sleeves 60 not only bias the retainer 16, 18 to return to its original tubular shape, they also provide the patient with some protection against abrasions which may be caused the structure of the filaments 44, 46. With the addition of a biasing sleeve 66 over the entire inner surface 64, the retainer 16 assumes the embodiment shown in Figure 7C. For another embodiment, Figure 7D shows that the sleeve 60 may extend past the proximal end 28 and past the distal end 32 of the retainer 16. In Figure 7E, the sleeve 60 is shown to be bifurcated in order to cover proximal end 28 with only a sleeve portion 60a and to cover distal end 32 with only a sleeve portion 60b. The embodiment of Figure 7F shows an embodiment wherein the sleeve 60 on the outer surface 62 is integral with the sleeve 66 on the inner surface 64. For this embodiment, the filaments 44, 46 are effectively embedded between the sleeves 60, 66. The embodiment of Figure 7G is similar to that shown in Figure 7D, with the difference being that the sleeve 66 on inner surface 64 extends beyond the proximal end 28 and the distal end 32, and not vice versa. Finally, the embodiment for the retainer 16 shown in Figure 7H shows an integral connection between sleeve portions 60/66a at the proximal end 28 of retainer 16, and sleeve portions 60/66b at the distal end 32 of the retainer 16. It will be appreciated that still other variations in the embodiments of retainers 16, 18 are possible.

[0026] Fig 8 shows the system 10 of the present invention incorporating the particular embodiment for retainers 16, 18 that is depicted in Fig. 7H. As shown in Fig. 8, each of these retainers 16, 18 has a segment 68

which includes braided filaments 44, 46. For this particular embodiment, however, the segment 68 of the braided filaments 44, 46 is bonded between extensions 70 and 72 of the sleeve 66. As can be appreciated by the skilled artisan, these extensions 70, 72 can be made of an elastomeric material, such as a PEBAX® material disclosed above.

Claims

1. A system for selectively holding a stent (14) on a delivery catheter (20) which comprises:

an inflatable balloon (12) defining a longitudinal axis;
a first plurality of mutually juxtaposed filaments (44);
a second plurality of mutually juxtaposed filaments (46) woven with said first plurality of filaments (44) to create a braided tube (16) having a proximal end and a distal end with a length therebetween;
means for anchoring said proximal end (28) of said braided tube (16) to said balloon (12) to position said distal end of said tube over a proximal portion of said stent (14) when said stent is mounted on said balloon to hold said stent against said balloon, said tube being positioned with said filaments of said first plurality helically disposed with a positive pitch relative to said axis and said filaments of said first plurality helically disposed with a positive pitch relative to said axis and said filaments of said second plurality helically disposed with a negative pitch relative to said axis; and
means for inflating said balloon (12) to urge said balloon against said tube (16) to increase said positive pitch and increase said negative pitch of respective said filaments to shorten said length of said tube to withdraw said tube from said stent to release said stent from said balloon.

2. A system as recited in claim 1 wherein said braided tube (16) is a first tube and said system further comprises:

a second said braided tube (18), and
means for anchoring said distal end (30) of said second tube to said balloon (12) to position said proximal end of said second tube over a distal portion of said stent (14) when said stent is mounted on said balloon, with said positive pitch and said negative pitch of respective said filaments being increased by inflation of said balloon to shorten said length of said tube to withdraw said tube from said stent to release said stent from said balloon.

3. A system as recited in claim 1 or 2 wherein said braided tube (16, 18) has an inner surface and an outer surface, and wherein said system further comprises an elastomeric sleeve (60) covering at least a portion of said outer surface, said sleeve being biased by inflation of said balloon (12) to decrease said positive pitch and to decrease said negative pitch of respective said filaments to lengthen said tube and collapse said balloon to separate said tube and said balloon from said stent (14) after said stent is deployed and said balloon is deflated.
4. A system as recited in claim 1 or 2, wherein said braided tube (16, 18) has an inner surface and an outer surface, and wherein said system further comprises an elastomeric sleeve (60) positioned against at least a portion of said inner surface, said sleeve being biased by inflation of said balloon (12) to decrease said positive pitch and to decrease said negative pitch of respective said filaments to lengthen said tube and collapse said balloon to separate said tube and said balloon from said stent (14) after said stent is deployed and said balloon is deflated.
5. A system as recited in claim 1 or 2 wherein said braided tube (16, 18) has an inner surface and an outer surface, and wherein said retainer further comprises a first elastomeric sleeve positioned against at least a portion of said outer surface and a second elastomeric sleeve positioned against at least a portion of said inner surface, said first and second sleeves being biased by inflation of said balloon (12) to act in concert to decrease said positive pitch and to decrease said negative pitch of respective said filaments to lengthen said tube and collapse said balloon to separate said tube and said balloon from said stent (14) after said stent is deployed and said balloon is deflated.
6. A system as recited in any preceding claim wherein said filaments (44, 46) are each made of an impregnated elastomer to make said filaments lubricious.
7. A system as recited in any of claims 1 to 5, wherein said filaments (44, 46) are each made of a metallic material.
8. A system as recited in any of claims 1 to 5 wherein said filaments (44, 46) are each made of a composite including an elastomeric material PEBAX 5533 with approximately twenty five percent graphite.
9. A stent delivery balloon catheter system which comprises:
 - a catheter (20),
10. A stent delivery balloon catheter system which comprises:
 - an inflatable balloon (12) having a first and a second end with a working section therebetween, said balloon defining a longitudinal axis;
 - a stent (14) having a first end and a second end, said stent being positioned on said balloon over said working section; and
 - a tubular shaped retainer (16) having a first end and a second end and being moveable between a first configuration wherein said retainer has a first length and a second configuration wherein said retainer has a second length, said first length being greater than said second length, and further wherein said retainer has said first end thereof anchored to said catheter (20) and said second end thereof overlaps a portion of said stent (14) to hold said stent on said balloon (12) while said balloon is deflated and said retainer (16) is in said first configuration, said second end of said retainer withdrawing from said stent to release said stent from said catheter when said balloon is inflated to move said retainer into said second configuration.
11. A system as recited in claim 10 wherein said proximal retainer (16) and said distal retainer (18) are
 - an inflatable balloon (12) having a proximal cone and a distal cone with a working section therebetween;
 - a stent (14) having a proximal end and a distal end, said stent being positioned on said balloon over said working station;
 - a proximal retainer (16) having a proximal end and a distal end with said proximal end thereof anchored to said balloon to position said proximal retainer over said proximal cone of said balloon and position said distal end thereto in an overlapping relationship with said proximal end of said stent, said proximal retainer having a length;
 - a distal retainer (18) having a proximal end and a distal end with said distal end thereof anchored to said balloon to position said distal retainer over said distal cone of said balloon to position said distal retainer over said distal cone of said balloon and position said proximal end thereof in an overlapping relationship with said distal end of said stent, said distal retainer having a length; and
 - means for inflating said balloon to shorten said respective lengths of said proximal retainer and said distal retainer to release said stent from said system as said stent is deployed by inflation of said balloon.

respectively moveable between a first configuration wherein said retainer has a first length, and a second configuration wherein said retainer has a second length, said first length being greater than said second length, and further wherein said retainer has said first end thereof anchored to said catheter (20) and said second end thereof overlapping a portion of said stent (14) to hold said stent on said balloon while said balloon (12) is deflated and said retainer is in said first configuration, said second end of said retainer withdrawing from said stent to release said stent from said catheter when said balloon is inflated to move said retainer into said second configuration.

12. A system as recited in claim 9, 10 or 11 wherein said balloon defines a longitudinal axis and said retainer (16) comprises:

a first plurality of mutually juxtaposed filaments (44), and
a second plurality of mutually juxtaposed filaments (46) woven with said first plurality of filaments to create a braided tube (16), said tube being positioned with said filaments of said first plurality helically disposed with a positive pitch relative to said axis and said filaments of said second plurality helically disposed with a negative pitch relative to said axis, there being an increase in said positive pitch and an increase in said negative pitch of respective said filaments when said retainer moves from said first configuration to said second configuration.

13. A system as recited in claim 9, 10, 11 or 12 wherein said retainer (16) has an inner surface and an outer surface, and wherein said system further comprises an elastomeric sleeve (60) covering at least a portion of said outer surface, said sleeve being biased by inflation of said balloon (12) to return said retainer from said second configuration to said first configuration to lengthen said tube and collapse said balloon to separate said tube and said balloon from said stent (14) after said stent is deployed and said balloon is deflated.

14. A system as recited in any of claims 9 to 12 wherein said retainer (16) has an inner surface and an outer surface, and wherein said retainer further comprises an elastomeric sleeve positioned against at least a portion of said inner surface, said sleeve being biased by inflation of said balloon (2) to return said retainer from said second configuration to said first configuration to lengthen said tube and collapse said balloon to separate said tube and said balloon from said stent (14) after said stent (14) is deployed and said balloon is deflated.

15. A system as recited in any of claims 9 to 12 wherein said retainer (16) has an inner surface and an outer surface, and wherein said retainer further comprises a first elastomeric sleeve positioned against at least a portion of said inner surface, said first and second sleeves being biased by inflation of said balloon (12) to act in concert to return said retainer from said second configuration to said first configuration to lengthen said tube and collapse said balloon to separate said tube and said balloon from said stent (14) after said stent is deployed and said balloon is deflated.




Figure 1




Figure 2




Figure 3A




Figure 3B




Figure 4A




Figure 4B




Figure 5





Figure 8



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 10 4536

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 549 635 A (SOLAR RONALD J) 27 August 1996 (1996-08-27)	9-11	A61F2/06
A	* column 6, line 13 - column 7, line 9; figures *	1,2	
X	EP 0 442 657 A (BARD INC C R) 21 August 1991 (1991-08-21)	9-11	
A	* column 7, line 24 - column 9, line 55; figures *	1	
X	WO 98 07390 A (SCIMED LIFE SYSTEMS INC) 26 February 1998 (1998-02-26)	9	
A	* page 31, line 9 - page 33, line 7; figures 38-42 *	1,10,11	
A	US 5 776 141 A (OVERBEEK-BLOEM MARTIN ET AL) 7 July 1998 (1998-07-07)	1,9,10	
	* column 11, line 66 - column 12, line 29; figures *		
D,A	US 4 950 227 A (SAVIN MICHAEL A ET AL) 21 August 1990 (1990-08-21)	1,9,10	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
	* column 4, line 1 - line 57; figures *		A61F A61M
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 June 2000	Examiner Kousouretas, I
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 4536

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-06-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5549635 A	27-08-1996	US 5403341 A	04-04-1995
		EP 0819015 A	21-01-1998
		JP 11503341 T	26-03-1999
		WO 9631249 A	10-10-1996
EP 0442657 A	21-08-1991	US 5108416 A	28-04-1992
		AU 7097791 A	15-08-1991
		JP 7051382 A	28-02-1995
WO 9807390 A	26-02-1998	US 6007543 A	28-12-1999
		AU 4162597 A	06-03-1998
		EP 0932377 A	04-08-1999
		US 5968069 A	19-10-1999
		US 5944726 A	31-08-1999
US 5776141 A	07-07-1998	AU 6960196 A	19-03-1997
		EP 0847259 A	17-06-1998
		JP 11511361 T	05-10-1999
		WO 9707756 A	06-03-1997
US 4950227 A	21-08-1990	DE 68927998 D	28-05-1997
		DE 68927998 T	11-09-1997
		EP 0409929 A	30-01-1991
		JP 2935561 B	16-08-1999
		JP 6503481 T	21-04-1994
		WO 9005554 A	31-05-1990

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.